



IMPORTANT NOTES TO READ...!!!

- 3 PERSONS + DRIVER REQUIRED TO HANDLE TANK.
- Drawing shows all available outlet & overflow positions. Standard installations have only 1 outlet & 1 overflow.
- Please refer to 'Easy 6 Step Tank Installation Guide' for instruction to install accessories.
- All dimensions are in Metres and rounded to the nearest Centimetre.
- Capacities & measurements are tested in accordance with AS4766, but may vary due to roto-moulding process.
- Bushmans recommends top and sides clearance of 100mm minimum when estimating space required for tank.

<h2>BUSHMANS SALES DRAWING</h2> <p>Level 13, 300 GEORGE STREET, SYDNEY, NSW 2000 Ph 1800 00 88 88 Fax 02 9233 1363 WWW.BUSHMANTANKS.COM.AU</p>	<p>Copyright 2010 Bushmans Group Pty Ltd. This drawing may not be reproduced or transmitted in any form or by any means in part or whole without written permission of Bushmans Group Pty Ltd.</p>	Drawn BUSH ENG	Project Title TSL440 SLIM	<p>Drawing Title TSL440 SLIM 2000Litre Tank</p>
		Date JUL-2010	Material POLYETHYLENE	
		Scale Not to Scale	Finish -----	A4 Size Drawing Sheet 1 of 1