



IMPORTANT NOTES TO READ...!!!

- **3 PERSONS + DRIVER REQUIRED TO HANDLE TANK.**
- DRAWING SHOWS ALL AVAILABLE OUTLET & OVERFLOW POSITIONS. STANDARD INSTALLATIONS HAVE ONLY 1 OUTLET & 1 OVERFLOW
- PLEASE REFER TO 'EASY 6 STEP TANK INSTALLATION GUIDE' FOR INSTRUCTION TO INSTALL ACCESSORIES.
- ALL DIMENSIONS ARE IN METRES AND ROUNDED TO THE NEAREST CENTIMETRE.
- CAPACITIES AND MEASUREMENTS ARE TESTED IN ACCORDANCE TO AS4766, BUT MAY VARY DUE TO THE ROTO-MOULDING PROCESS.
- BUSHMANS RECOMMENDS TOP AND SIDES CLEARANCE OF 100MM MINIMUM WHEN ESTIMATING SPACE REQUIRED FOR THE TANK.

BUSHMANS GROUP PTY LTD
 300 GEORGE STREET, SYDNEY, NSW 2000
 Ph 1800 00 88 88 WWW.BUSHMANTANKS.COM .AU

Copyright 2012 Bushmans Group Pty Ltd. This drawing may not be reproduced or transmitted in any form or by any means in part or whole without written permission of Bushmans Group Pty Ltd.

Drawn	S.NAGY	Project Title	TXD5000 V004
Date	31.03.15	Material	POLYETHYLENE
Scale	1:50	Finish	

Drawing Title	TXD5000 ROUND 22500 LITRE TANK TANK SALES DRAWING
A4 Size Drawing	Sheet 1 of 1